

PODIUM 500

PODIUM 500

This unit is ideal for all trades to help get to those just out of reach places without difficulty. Ideal for installation, maintenance or snagging at the end of the job.

Suitable for use on flat ground, providing platform levels of 0.25m and 0.50m

Unique Features:

- 2 working heights, 2.25m and 2.50m
- Easy to assemble in minutes
- Platform area ideal size for one person and tools.
- Folds flat to fit in a van for easy transport and storage.
- Open or folded the unit easily passes through a standard door,
- Non slip platform board.
- Gated access to allow ease of entry and exiting to and from the unit



EURO TOWERS LTD

UK Manufacturer of Aluminium Access Equipment

Tel: +44 (0) 1604 644 774 | Web: www.EuroTowers.co.uk | Email: Sales@eurotowers.co.uk
Euro Towers Ltd, Unit 5, Edgemoor Close, Round Spinney Ind Est, Northampton, NN3 8RG



STEPFOLD 500 PODIUM

STEPFOLD 500 PODIUMS Assembly Instructions

- Ensure all parts are present and are not damaged before assembling.
- This unit is not designed for heavy loads.
- One person unit only.
- Please ensure that any weight is dispersed as evenly as possible

COMPRISING OF...

- 4 x 5" Castor C/w Adaptor (OR 2 x Castors & 2 x Anti Surf Base Plates)
- 1 x Podium 500 Base Unit
- 1 x Podium 500 Platform
- 1 x Podium 500 Step Brace
- 1 x SPOD Stabiliser Left
- 1 x SPOD Stabiliser Right

	Stepfold 500 Podium
Platform Height	0.5m
Safe Working Load	150Kg

REMEMBER YOUR SAFETY DEPENDS ON THE SAFE ASSEMBLY AND USE OF THIS EQUIPMENT. ALWAYS CLOSE THE GATE.

General Safety Rules:

1. Do not use if the product is damaged or has parts missing
2. Do not use on unstable ground such as loose bricks, boxes or blocks
3. Always check the unit is level before use.
4. Remove all personnel and materials before moving the unit.
5. Do not gain extra height by using boxes, ladders etc. on the platform.
6. If there is an overhead hazard use head protection.
7. Do not overload the unit.
8. Do not overreach out of the unit
9. Engage all stabilizers in their correct position before use on staircases.
10. Never climb the outside of the unit.
11. Never use the guardrails to gain extra height.

Maximum safe working load 150Kg

This unit can also be converted into a Stairpod 500 Podium, Please contact us for more information with how to proceed.



1. Open the base unit out and lock the back section making sure you press the trigger.

2. Place your platform on the required rung and lock both castors.

3. When working at 0.5m add your brace above the first rung with hooks facing out.

3. Fit your left and right stabilisers to the front of the unit.

5. Enter the unit climbing the step brace keeping 3 points of contact. Then close the gate ensuring the kliker is engaged.



Dismantling is reverse of assembly

EURO TOWERS LTD

UK Manufacturer of Aluminium Access Equipment

Tel: +44 (0) 1604 644 774 | Web: www.EuroTowers.co.uk | Email: Sales@eurotowers.co.uk
Euro Towers Ltd, Unit 5, Edgemoad Close, Round Spinney Ind Est, Northampton, NN3 8RG

